

# MURRO II






  
**AMERLUX**  
LIGHTING SOLUTIONS  
ADAPT. ABILITY.™

# MURRO II

## MURRO II

**Murro II™** provides high-performance wall washing for retail and commercial applications. Featuring a low-profile design and durable die-cast aluminum construction, Murro II provides the look and quality suitable for any space. Murro II is available in ED17 and T6 ceramic metal halide lamping, electronic or magnetic ballast, and offers a host of user-friendly features. Optically, Murro II features a custom-configured, textured reflector and specially designed lens that provide even, intense washes of light, even at center-to-center spacing up to 10 feet, allowing Murro II to fit any energy or budget requirement.



### Lamping

Murro II is available for use with ED17 and T6 ceramic metal halide lamps.

#### ED17 Medium Base

| Lamp Wattage | Initial Lumens | Lamp Life (hrs) |
|--------------|----------------|-----------------|
| 50           | 4250           | 16000           |
| 70           | 6200           | 16000           |
| 100          | 9300           | 16000           |

#### T6 G12 Bi-Pin Base

| Lamp Wattage | Initial Lumens | Lamp Life (hrs) |
|--------------|----------------|-----------------|
| 39           | 3400           | 12000           |
| 70           | 6600           | 12000           |

Data Shown:  
Philips Lighting 3000K CCT



Captive lamp housing door with locking knob provides hands-free relamping.

Low-profile design allows fixture to be closer to the track.



Aiming angle indicator allows for precise aiming of fixture head.

**AMERLUX®**  
LIGHTING SOLUTIONS

ADAPT. ABILITY.™



## MURRO II

### FEATURES

#### CONSTRUCTION

Die-cast aluminum construction

Low-profile design

Aiming angle indicator

Locking vertical adjustment  
0-90 degrees

Captive lamp housing door with  
locking knob

Available in over 200 durable, powder  
coat painted finishes

#### OPTICS

High-performance optics

Specially designed optics both for  
ED17 and T6

Optional tinted reflector finishes

### BENEFITS

Allows for precise optical alignment of lamp,  
reflector and lens for improved lighting  
performance and consistency between fixtures.  
Eliminates light leaks for less obtrusive look.

Allows for fixture to be closer to track for a less  
obtrusive look.

Allows for precise aiming of fixture head on  
product displays.

Keeps aiming position and allows lighting to remain  
as designed even through relamping cycles.

Permits hands-free relamping.

Provides unmatched palette for any design.

Maximize performance from each lamp type.

Allow warming of standard 3000K ceramic metal  
halide light to a variety of incandescent-like hues.

### PERFORMANCE

#### ED17 70W

Footcandles on Wall

##### Track 3 Feet From Wall

| Distance From Ceiling | 6'  |    |     |
|-----------------------|-----|----|-----|
|                       | 1'  | 2' | 3'  |
| 1'                    | 115 | 40 | 115 |
| 2'                    | 142 | 62 | 142 |
| 3'                    | 104 | 66 | 104 |
| 4'                    | 72  | 58 | 72  |
| 5'                    | 52  | 48 | 52  |
| 6'                    | 40  | 38 | 40  |
| 7'                    | 32  | 31 | 32  |
| 8'                    | 27  | 27 | 27  |
| 9'                    | 24  | 24 | 24  |

##### Track 4 Feet From Wall

| Distance From Ceiling | 6'  |    |     |
|-----------------------|-----|----|-----|
|                       | 1'  | 2' | 3'  |
| 1'                    | 76  | 48 | 76  |
| 2'                    | 101 | 68 | 101 |
| 3'                    | 90  | 73 | 90  |
| 4'                    | 71  | 66 | 71  |
| 5'                    | 56  | 54 | 56  |
| 6'                    | 46  | 45 | 46  |
| 7'                    | 37  | 37 | 37  |
| 8'                    | 32  | 32 | 32  |
| 9'                    | 27  | 27 | 27  |

##### Track 4 Feet From Wall

| Distance From Ceiling | 8' |    |    |
|-----------------------|----|----|----|
|                       | 1' | 2' | 3' |
| 1'                    | 71 | 25 | 71 |
| 2'                    | 94 | 36 | 94 |
| 3'                    | 81 | 42 | 81 |
| 4'                    | 60 | 41 | 60 |
| 5'                    | 45 | 37 | 45 |
| 6'                    | 35 | 32 | 35 |
| 7'                    | 28 | 27 | 28 |
| 8'                    | 23 | 23 | 23 |
| 9'                    | 20 | 20 | 20 |

For 50w data, multiply by .69

For 100w data, multiply by 1.5

For T6 photometry, consult specification sheet

#### ORDERING INFORMATION Example: MUR II-70-17-E-W-TN3-120-WW

| CAT #  | WATTAGE         | LAMP TYPE | BALLAST                        | COLOR  | MOUNTING  | VOLTAGE    | BEAM SPREAD    | OPTIONS/ACCESSORIES                                     |
|--------|-----------------|-----------|--------------------------------|--|---|------------|----------------|---|
| MUR II | 50<br>70<br>100 | 17 - ED17 | E - electronic<br>M - magnetic | B - black<br>W - white<br>____ - ____<br>(other RAL) | TA1 - A-Track 1 cir<br>TN1 - Global 1 cir<br>TN2 - Global 2 cir/<br>2 neutral<br>TN3 - Global 3 cir | 120<br>277 | WW - wall wash | SUN - sunrise reflector<br>GOLD - ferric gold reflector |
|        | 39<br>70        | T6        |                                |  | B - Busway<br>C - Canopy<br>CCL - c-clamp<br>____ - ____<br>(other)                                 |            |                |   |

**AMERLUX**  
LIGHTING SOLUTIONS

ADAPT. ABILITY.™

