

# DECORATIVE FIXTURES

## exterior\_fixed\_unlensed

exterior



CRE2601 MICRO MINI BOLLARD	
<b>Max. Overall Dimensions:</b>	4" OD x 3.324" H (102MM OD x 84.4MM H)
<b>Trim/Flange Dimensions:</b>	4" OD x 0.254" H (102MM OD x 6.45MM H)
<b>Aperture Dimensions:</b>	2" OD (50.8MM OD)
<b>Rough-in:</b>	1.378" (35MM)
<b>Recess:</b>	1.25" (31.8MM)
<b>FSPT Fibers:</b>	50 (MAX.)
<b>Ferrules:</b>	8MM
<b>Finish Options:</b>	BLACK, STAINLESS STEEL

<b>Prime Material:</b>	ALUMINUM AND ACRYLIC
<b>Mounting:</b>	SCREWS

exterior



CRE2602 MICRO DECORATIVE FLAT BOLLARD	
<b>Max. Overall Dimensions:</b>	4" OD x 2.521" H (102MM OD x 64.03MM H)
<b>Trim/Flange Dimensions:</b>	4" OD x 0.254" H (102MM OD x 6.45MM H)
<b>Aperture Dimensions:</b>	2" OD (50.8MM OD)
<b>Rough-in:</b>	1.378" (35MM)
<b>Recess:</b>	1.25" (31.8MM)
<b>FSPT Fibers:</b>	50 (MAX.)
<b>Ferrules:</b>	8MM
<b>Finish Options:</b>	BLACK, STAINLESS STEEL

<b>Prime Material:</b>	ALUMINUM AND ACRYLIC
<b>Mounting:</b>	SCREWS

exterior



CRE2603 MICRO LATERAL FLAT BOLLARD	
<b>Max. Overall Dimensions:</b>	4" OD x 2.521" H (102MM OD x 64.03MM H)
<b>Trim/Flange Dimensions:</b>	4" OD x 0.254" H (102MM OD x 6.45MM H)
<b>Aperture Dimensions:</b>	2" OD (50.8MM OD)
<b>Rough-in:</b>	1.378" (35MM)
<b>Recess:</b>	1.25" (31.8MM)
<b>FSPT Fibers:</b>	50 (MAX.)
<b>Ferrules:</b>	8MM
<b>Finish Options:</b>	BLACK, STAINLESS STEEL

**Technical Remarks:**  
Fixture allows lateral light out of sides and top.

<b>Prime Material:</b>	ALUMINUM AND ACRYLIC
<b>Mounting:</b>	SCREWS

exterior



CRE2604 MICRO DOMED FLAT BOLLARD	
<b>Max. Overall Dimensions:</b>	4" OD x 2.134" H (102MM OD x 54.2MM H)
<b>Trim/Flange Dimensions:</b>	4" OD x 0.254" H (102MM OD x 6.45MM H)
<b>Aperture Dimensions:</b>	2" OD (50.8MM OD)
<b>Rough-in:</b>	1.378" (35MM)
<b>Recess:</b>	1.25" (31.8MM)
<b>FSPT Fibers:</b>	50 (MAX.)
<b>Ferrules:</b>	8MM
<b>Finish Options:</b>	BLACK, STAINLESS STEEL

<b>Prime Material:</b>	ALUMINUM AND ACRYLIC
<b>Mounting:</b>	SCREWS

# UNDERWATER FIXTURES

## exterior\_fixed\_lensed



underwater



LNS-100 UNDERWATER LENSED FIXTURE	
<b>Max. Overall Dimensions:</b>	3.5" OD x 1.75" H (88.9MM OD x 44.4MM H)
<b>Lens Dimensions:</b>	2.18" OD (55.4MM OD)
<b>Rough-in:</b>	2" (50.8MM)
<b>FSPT Fibers:</b>	100 (MAX.)
<b>Ferrules:</b>	INCLUDED
<b>Finish Options:</b>	BLACK, WHITE

**Technical Remarks:**  
Available for use with 75 fibers maximum (LNS-100G-white finish, LNS-100BLG-black finish, and LNS-100A-white finish with locking nut). A lens tightening tool (FS-117) is required for installation and must be ordered separately. Comes with fresnel lens or optional broadcast lens (B11458).

<b>Prime Material:</b>	PLASTIC
<b>Mounting:</b>	CONDUIT, STUBBING TO 1.5" PVC

underwater



LNS-225 UNDERWATER LENSED FIXTURE	
<b>Max. Overall Dimensions:</b>	3.5" OD x 1.75" H (88.9MM OD x 44.4MM H)
<b>Lens Dimensions:</b>	2.18" OD (55.4MM OD)
<b>Rough-in:</b>	2" (50.8MM)
<b>FSPT Fibers:</b>	225 (MAX.)
<b>Ferrules:</b>	INCLUDED
<b>Finish Options:</b>	BLACK, WHITE

**Technical Remarks:**  
Available for use with 225 fibers (LNS-225G-white finish, and LNS-225A-white finish with locking nut). A lens tightening tool (FS-117) is required for installation and must be ordered separately. Comes with fresnel lens or optional broadcast lens (B11458).

<b>Prime Material:</b>	PLASTIC
<b>Mounting:</b>	CONDUIT, STUBBING TO 1.5" PVC

underwater



LBM06102030S2 UNDERWATER LENSED FIXTURE	
<b>Max. Overall Dimensions:</b>	3.973" OD x 2.362" H (100MM OD x 60MM H)
<b>Trim/Flange Dimensions:</b>	3.973" OD x 0.394" H (100MM OD x 10MM H)
<b>Aperture Dimensions:</b>	2.205" OD (56MM OD)
<b>Rough-in:</b>	2.441" (62MM)
<b>Recess:</b>	1.969" (50MM)
<b>FSPT Fibers:</b>	150 (MAX.)
<b>Ferrules:</b>	8MM, 10MM
<b>Beam Spread:</b>	85 (MIN.) – 85 (MAX.)
<b>Finish Options:</b>	STAINLESS STEEL

**Technical Remarks:**  
Material is V4A stainless steel, resistant to salt water. Comes with LBM06102000 'LNS 100V4A Installation Kit', LBM061020301 'LNS 100V4A Mounting Sleeve', and LBM061020302 'LNS100V4A Pour-In-Ring'.

<b>Prime Material:</b>	STAINLESS STEEL
<b>Mounting:</b>	REFER TO TECHNICAL REMARKS

underwater



CRE2153 LENSED FOUNTAIN SPOTLIGHT	
<b>Max. Overall Dimensions:</b>	1.063" OD x 3.15" H (27MM OD x 80MM H)
<b>Trim/Flange Dimensions:</b>	1.063" OD (27MM OD)
<b>Aperture Dimensions:</b>	1" OD (25.4MM OD)
<b>FSPT Fibers:</b>	75 (MAX.)
<b>Ferrules:</b>	8MM, 10MM
<b>Beam Spread:</b>	17 (MIN.) – 17 (MAX.)
<b>Finish Options:</b>	STAINLESS STEEL

**Technical Remarks:**  
Mount to fountain head with 1" pipe clamp, or secure to any object with appropriate device.

<b>Prime Material:</b>	STAINLESS STEEL
<b>Mounting:</b>	PIPE CLAMP BY OTHERS

underwater



LBM061208202 MINI-FOUNTAIN FITTING	
<b>Max. Overall Dimensions:</b>	1.338" OD x 1.693" H (34MM OD x 43MM H)
<b>Trim/Flange Dimensions:</b>	1.338" OD x 0.079" H (34MM OD x 2MM H)
<b>Aperture Dimensions:</b>	0.75" OD (19MM OD)
<b>Rough-in:</b>	1" (25.4MM)
<b>Recess:</b>	1.496" (38MM)
<b>FSPT Fibers:</b>	75 (MAX.)
<b>Ferrules:</b>	8MM, 10MM
<b>Beam Spread:</b>	15 (MIN.) – 35 (MAX.)
<b>Finish Options:</b>	STAINLESS STEEL

**Technical Remarks:**  
Adhere inside 1-1/4" PVC pipe or directly into wall or floor of pool/pond/fountain with Fiberstars silicon adhesive (FS-136 or FS-138).

<b>Prime Material:</b>	STAINLESS STEEL
<b>Mounting:</b>	REFER TO TECHNICAL REMARKS

# UNDERWATER FIXTURES

## exterior\_fixed\_lensed

underwater



<b>LBM06120819, LBM06120820</b> <small>LENSED FOUNTAIN SPOTLIGHT</small>	
<b>Max. Overall Dimensions:</b> 1.772" OD x 1.693" H (45MM OD x 30MM H)	
<b>Trim/Flange Dimensions:</b> 1.772" OD x 0.118" H (45MM OD x 3MM H)	
<b>Aperture Dimensions:</b> 0.75" OD (19MM OD)	
<b>Rough-in:</b> 0.866" (22MM)	<b>Beam Spread:</b> 15 (MIN.) – 35 (MAX.)
<b>Recess:</b> 1.063" (27MM)	<b>Finish Options:</b> STAINLESS STEEL - 819
<b>FSPT Fibers:</b> 75 (MAX.)	BRONZE - 820
<b>Ferrules:</b> 8MM, 10MM	

**Technical Remarks:**  
Adhere inside 1" PVC pipe with Fiberstars silicon adhesive (FS-136 or FS-138).

<b>Prime Material:</b>	STAINLESS STEEL
<b>Mounting:</b>	REFER TO TECHNICAL REMARKS

# UNDERWATER FIXTURES

## exterior\_adjustable\_lensed



underwater



<b>LBM06102120</b> <small>RECESSED UNDERWATER ACCENT</small>	
<b>Max. Overall Dimensions:</b> 4.75" OD x 5.12" H (121MM OD x 130MM H)	
<b>Trim/Flange Dimensions:</b> 4.75" OD x 1.19" H (121MM OD x 30.2MM H)	
<b>Aperture Dimensions:</b> 0.75" OD (19MM OD)	
<b>Rough-in:</b> 3" (76.2MM)	<b>Beam Spread:</b> 15 (MIN.) – 35 (MAX.)
<b>Recess:</b> 4" (102MM)	<b>Rotation Angle:</b> 360
<b>FSPT Fibers:</b> 75 (MAX.)	<b>Max. Tilt Angle:</b> +/- 30
<b>Ferrules:</b> 8MM, 10MM	<b>Finish Options:</b> STAINLESS STEEL

**Technical Remarks:**  
Adheres inside PVC pipe or directly into wall or floor of pool/pond/fountain with Fiberstars silicon adhesive (FS-136 or FS-138).

<b>Prime Material:</b>	STAINLESS STEEL
------------------------	-----------------

underwater



<b>LBM06102121</b> <small>YOKE MOUNTED UNDERWATER ACCENT</small>	
<b>Max. Overall Dimensions:</b> 2.19" OD x 2.81" H (55.6MM OD x 71.4MM H)	
<b>Aperture Dimensions:</b> 0.792" OD (20.12MM OD)	
<b>FSPT Fibers:</b> 75 (MAX.)	<b>Beam Spread:</b> 15 (MIN.) – 35 (MAX.)
<b>Ferrules:</b> 8MM, 10MM	<b>Rotation Angle:</b> 360
	<b>Max. Tilt Angle:</b> +/- 90
	<b>Finish Options:</b> STAINLESS STEEL

<b>Prime Material:</b>	STAINLESS STEEL
<b>Mounting:</b>	YOKE